



www.qingdaohawktyre.com

NEW OCEAN TRADING COMPANY LIMITED
Thuong Khuong, Vinh Hung commune,
Binh Giang district, Hai Duong province, Vietnam
Tel: (+84) 098-307-1240
Email: congydaiduongmoi@gmail.com



**PREMIUM TYRE
MANUFACTURER**
SINCE 1975



HLS1



Tyre Size	Ply Rating	Tread Depth (mm)	Standard Rim	Tube Type	Load Index	Speed Symbol	Overall Diameter (mm)	Section Width (mm)	Inflation Pressure(kpa)		Load Capacity(kg)	
									Single	Dual	Single	Dual
295/80R22.5	18PR	16.0	9.00	TL	152/149	M	1044	298	900	900	3550	3250
315/80R22.5	20PR	16.0	9.00	TL	156/150	L	1096	318	850	850	4000	3550

Performance Description: **⚠ Only fit for tractor and trailer**

- Super Wide and Extremely wear-resistant.
- Special designed for long haul. Perform well on good road condition high speed.
- Contact Area 10% bigger than regular design.
- Larger footprint for drive comfort and long tread wear.
- Strong bead structure insures longer endurance and lifespan.



HK707 / HK707+



Tyre Size	Ply Rating	Tread Depth (mm)	Standard Rim	Tube Type	Load Index	Speed Symbol	Overall Diameter (mm)	Section Width (mm)	Inflation Pressure(kpa)		Load Capacity(kg)	
									Single	Dual	Single	Dual
11.00R20	18PR	25.0	8.00	TT	152/149	B	1085	295	930	930	3550	3250
12.00R20	20PR	25.0	8.50	TT	156/153	B	1125	315	900	900	4000	3650
12.00R20	22PR	25.0	8.50	TT	158/155	B	1125	315	970	970	4250	3875
12.00R24	24PR	25.0	8.50	TT	164/161	B	1226	315	900	900	5000	4625

Performance Description: **⚠ Off the road/Only fit for Mine truck**

- Applied for short-haul , low speed, and heavy loaded mine trucks.
- Excellent stab-resistance, anti-eccentric worn, avulsion resistance .
- Aggressive lug pattern design provides excellent grip and traction performance.



HK730G



Tyre Size	Ply Rating	Tread Depth (mm)	Standard Rim	Tube Type	Load Index	Speed Symbol	Overall Diameter (mm)	Section Width (mm)	Inflation Pressure(kpa)		Load Capacity(kg)	
									Single	Dual	Single	Dual
12R22.5	18PR	18.0	9.00	TL	152/149	L	1085	300	930	930	3550	3250

Performance Description: **⚠ Only fit for tractor and trailer**

- Super wide and extremely wear-resistant.
- Mixed highway and freeway for long distance and national transportation service.
- Contact area 10% bigger than regular design.
- Larger footprint for drive comfort and long tread wear.
- Enhanced channel siping and wide grooves allow for premium wet and dry traction.



HK701



Tyre Size	Ply Rating	Tread Depth (mm)	Standard Rim	Tube Type	Load Index	Speed Symbol	Overall Diameter (mm)	Section Width (mm)	Inflation Pressure(kpa)		Load Capacity(kg)	
									Single	Dual	Single	Dual
11.00R20	18PR	17.0	8.00	TT	152/149	K	1085	293	930	930	3550	3250
12.00R20	20PR	17.0	8.50	TT	156/153	K	1125	315	900	900	4000	3650
12.00R20	22PR	17.0	8.50	TT	156/153	K	1125	315	900	900	4250	3875
13R22.5	20PR	19.0	9.75	TL	156/153	J	1136	320	930	930	4000	3650

Performance Description: **⚠ Only fit for tractor and trailer**

- Applied for highway, urban and country road, all position tractor and trailer.
- Three rib pattern, extra sideslip resistance, delivers superior stability and drainage of driving.
- Super steel belt carcass construction enhances casing strength and maximizes tire load capacity.



HK710



Tyre Size	Ply Rating	Tread Depth (mm)	Standard Rim	Tube Type	Load Index	Speed Symbol	Overall Diameter (mm)	Section Width (mm)	Inflation Pressure(kpa)		Load Capacity(kg)	
									Single	Dual	Single	Dual
11.00R20	18PR	25.0	8.00	TT	152/149	B	1085	295	930	930	3550	3250
12.00R20	22PR	25.5	8.50	TT	158/155	B	1125	315	970	970	4250	3875

Performance Description: **⚠ Off the road/Only fit for Mine truck**

- Applied for short-haul , low speed and heavy loaded mine trucks.
- Special tread compound with high wear-resistance, suitable for mining application and construction sites.
- Aggressive lug pattern design provides excellent grip and traction performance.



HK732 / HK732+



Tyre Size	Ply Rating	Tread Depth (mm)	Standard Rim	Tube Type	Load Index	Speed Symbol	Overall Diameter (mm)	Section Width (mm)	Inflation Pressure(kpa)		Load Capacity(kg)	
									Single	Dual	Single	Dual
11.00R20	18PR	18.0	8.00	TT	152/149	K	1085	293	930	930	3550	3250
12.00R20	20PR	19.0	8.50	TT	156/153	K	1125	315	900	900	4000	3650
12.00R20	22PR	19.0	8.50	TT	156/153	K	1125	315	900	900	4250	3875

Performance Description: **⚠ Only fit for tractor and trailer**

- Applicable for driving wheels of tractor and trailer.
- Unique pattern design offers good pulling force.
- Special tread compound offers excellent cut-resistance.
- Suitable for short distance on mining, bad roads and good roads.



HK750 / HK750+



Tyre Size	Ply Rating	Tread Depth (mm)	Standard Rim	Tube Type	Load Index	Speed Symbol	Overall Diameter (mm)	Section Width (mm)	Inflation Pressure(kpa)		Load Capacity(kg)	
									Single	Dual	Single	Dual
11.00R20	18PR	19.0	8.00	TT	152/149	K	1085	293	930	930	3550	3250
12.00R20	20PR	20.0	8.50	TT	156/153	K	1125	315	900	900	4000	3650
12.00R20	22PR	20.0	8.50	TT	156/153	K	1125	315	900	900	4250	3875

Performance Description:

⚠ Only fit for tractor and trailer

- Applied for short-haul , low speed, and heavy loaded tractor and trailer.
- Special tread compound with high cut-resistant, suitable for mining application and construction sites.
- Aggressive block pattern design provides excellent grip and traction performance.



HK755



Tyre Size	Ply Rating	Tread Depth (mm)	Standard Rim	Tube Type	Load Index	Speed Symbol	Overall Diameter (mm)	Section Width (mm)	Inflation Pressure(kpa)		Load Capacity(kg)	
									Single	Dual	Single	Dual
12R22.5	18PR	17.5	9.00	TL	152/149	L	1085	300	930	930	3550	3250

Performance Description:

⚠ Only fit for tractor and trailer

- Super Wide and Extremely wear-resistant.
- Special designed for long haul. Perform well on good road condition high speed.
- Contact Area 10% bigger than regular design.
- Larger footprint for drive comfort and long tread wear.
- Strong bead structure insures longer endurance and lifespan.



HK782G



Tyre Size	Ply Rating	Tread Depth (mm)	Standard Rim	Tube Type	Load Index	Speed Symbol	Overall Diameter (mm)	Section Width (mm)	Inflation Pressure(kpa)		Load Capacity(kg)	
									Single	Dual	Single	Dual
12R22.5	18PR	19.0	9.00	TL	152/149	L	1085	300	930	930	3550	3250

Performance Description:

⚠ Only fit for tractor and trailer

- Applied for express way, highway and urban road, drive position of tractor and trailer.
- Special tread compound design for lower heat build-up, excellent puncture and cut resistance and minimized gasoline consumption.
- Super steel belt carcass construction enhances casing strength and maximizes tyre load capacity.



HK792



Tyre Size	Ply Rating	Tread Depth (mm)	Standard Rim	Tube Type	Load Index	Speed Symbol	Overall Diameter (mm)	Section Width (mm)	Inflation Pressure(kpa)		Load Capacity(kg)	
									Single	Dual	Single	Dual
12.00R20	20PR	25.0	8.50	TT	156/153	B	1125	315	900	900	4000	3650

Performance Description:

⚠ Off the road/Only fit for Mine truck

- Applicable for driving wheels, for short distance with low speed on mining and bad roads.
- Pattern design offers excellent pulling force.
- Special tread compound offers excellent cut resistance.
- Reinforced bead design provides excellent load capacity.



HK791



Tyre Size	Ply Rating	Tread Depth (mm)	Standard Rim	Tube Type	Load Index	Speed Symbol	Overall Diameter (mm)	Section Width (mm)	Inflation Pressure(kpa)		Load Capacity(kg)	
									Single	Dual	Single	Dual
12.00R20	20PR	25.0	8.50	TT	156/153	B	1125	315	900	900	4000	3650
12.00R20	22PR	25.0	8.50	TT	158/155	B	1125	315	970	970	4250	3875

Performance Description:

⚠ Off the road/Only fit for Mine truck

- Applicable for driving wheels, for short distance with low speed on mining and bad roads.
- Pattern design offers excellent pulling force.
- Special tread compound offers excellent cut resistance.
- Reinforced bead design provides excellent load capacity.



HK802



Tyre Size	Ply Rating	Tread Depth (mm)	Standard Rim	Tube Type	Load Index	Speed Symbol	Overall Diameter (mm)	Section Width (mm)	Inflation Pressure(kpa)		Load Capacity(kg)	
									Single	Dual	Single	Dual
11.00R20	18PR	15.5	8.00	TT	152/149	K	1085	293	930	930	3550	3250
12.00R20	20PR	16.0	8.50	TT	156/153	K	1125	315	930	930	4000	3650
12.00R24	20PR	16.0	8.50	TT	160/157	K	1226	315	930	930	4500	4125
11R22.5	16PR	17.5	8.25	TL	146/143	M	1054	279	830	830	3000	2725
11R24.5	16PR	17.5	8.25	TL	149/146	L	1104	279	830	830	3250	3000
295/80R22.5	18PR	17.5	9.00	TL	152/149	M	1044	298	900	900	3550	3250
12R22.5	18PR	17.0	9.00	TL	152/149	L	1085	300	930	930	3550	3150
315/80R22.5	20PR	17.5	9.00	TL	156/150	L	1076	312	850	850	4000	3350
	167/164				950				950	5450	5000	

Performance Description:

⚠ Only fit for tractor and trailer

- Applied for express way and urban road, all position of the tractor and trailer.
- It delivers superior stability and drainage of driving.
- Super steel belt carcass construction enhances casing strength and maximizes tire load capacity.



HK806



Tyre Size	Ply Rating	Tread Depth (mm)	Standard Rim	Tube Type	Load Index	Speed Symbol	Overall Diameter (mm)	Section Width (mm)	Inflation Pressure(kpa)		Load Capacity(kg)	
									Single	Dual	Single	Dual
385/65R22.5	20PR	15.0	11.75	TL	160/162	K	1072	389	930	---	4500	---
	22PR								950	---	4750	---

Performance Description:

⚠ Only fit for tractor and trailer

- Application for all position on mixed highway and freeway.
- Special tread compound provides low heating-up, smooth wear & cut resistance, and low rolling resistance.



HK808



Tyre Size	Ply Rating	Tread Depth (mm)	Standard Rim	Tube Type	Load Index	Speed Symbol	Overall Diameter (mm)	Section Width (mm)	Inflation Pressure(kpa)		Load Capacity(kg)	
									Single	Dual	Single	Dual
11.00R20	18PR	24.0	8.00	TT	152/149	B	1093	288	930	930	3550	3250
12.00R20	20PR	24.0	8.50	TT	156/153	B	1131	311	900	900	4000	3650
12.00R24	20PR	25.0	8.50	TT	160/157	B	1228	312	900	900	4500	4125

Performance Description:

⚠ Off the road/Only fit for Mine truck

- Applied for bad road conditions including mining application of heavy duty workloads, short haul, low speed.
- Large lug pattern design provides excellent grip performance, wear-resistant compound design provide super tread life.
- Excellent stab-resistance, anti-eccentric worn, avulsion resistance and tread wear ability.



HK828



Tyre Size	Ply Rating	Tread Depth (mm)	Standard Rim	Tube Type	Load Index	Speed Symbol	Overall Diameter (mm)	Section Width (mm)	Inflation Pressure(kpa)		Load Capacity(kg)	
									Single	Dual	Single	Dual
11.00R20	18PR	19.0	8.00	TT	152/149	K	1096	293	930	930	3550	3250
12.00R20	20PR	19.5	8.50	TT	156/153	K	1136	315	930	930	4000	3650

Performance Description:

⚠ Only fit for tractor and trailer

- Special tread compound and design enable low heat build-up, excellent puncture and cut resistance and minimized gasoline consumption.
- Super steel belt carcass construction enhances casing strength and maximizes tyre load capacity.
- Four ribs with transverse deep grooves optimize speed and traction performance, provides excellent performance on wet road surface.



HK839



Tyre Size	Ply Rating	Tread Depth (mm)	Standard Rim	Tube Type	Load Index	Speed Symbol	Overall Diameter (mm)	Section Width (mm)	Inflation Pressure(kpa)		Load Capacity(kg)	
									Single	Dual	Single	Dual
295/80R22.5	18PR	19.0	9.00	TL	152/149	L	1044	298	900	900	3550	3250

Performance Description:

⚠ Only fit for tractor and trailer

- Applied for national highway, standard highway with normal condition.
- Driving wheel of long haul tractor, good traction, braking and sideslip resistance.
- Extra deep tread provides excellent grip and driving capacity and also enhance tyre safety and abrasion resistance performance.



HK852



Tyre Size	Ply Rating	Tread Depth (mm)	Standard Rim	Tube Type	Load Index	Speed Symbol	Overall Diameter (mm)	Section Width (mm)	Inflation Pressure(kpa)		Load Capacity(kg)	
									Single	Dual	Single	Dual
11.00R20	18PR	18.5	8.00	TT	152/149	K	1085	293	930	930	3550	3250
12.00R20	20PR	18.5	8.50	TT	156/153	K	1125	315	900	900	4000	3650

Performance Description:

⚠ Only fit for tractor and trailer

- Applicable for drive axle on unpaved road.
- Robust tread block provides outstanding traction on mud road surface.
- Special groove design with stone ejector prevent from stone penetration.
- Durable tyre carcass and improved tread compound help to resist.



HK859



Tyre Size	Ply Rating	Tread Depth (mm)	Standard Rim	Tube Type	Load Index	Speed Symbol	Overall Diameter (mm)	Section Width (mm)	Inflation Pressure(kpa)		Load Capacity(kg)	
									Single	Dual	Single	Dual
11R22.5	16PR	23.5	8.25	TL	146/143	M	1054	279	830	830	3000	2725
295/80R22.5	18PR	19.0	9.00	TL	152/149	L	1044	298	900	900	3550	3250
315/80R22.5	20PR	20.5	9.00	TL	156/150	L	1076	312	850	850	4000	3350
	22PR				167/164	C			950	950	5450	5000

Performance Description:

⚠ Only fit for tractor and trailer

- Open shoulder drive tire applied for urban and country road, drive position, reinforced
- steel belt carcass enhances casing strength and maximizes load capacity.
- Special wear-resistant tread design of low heat build-up.



HK810



Tyre Size	Ply Rating	Tread Depth (mm)	Standard Rim	Tube Type	Load Index	Speed Symbol	Overall Diameter (mm)	Section Width (mm)	Inflation Pressure(kpa)		Load Capacity(kg)	
									Single	Dual	Single	Dual
11R22.5	16PR	24.5	8.25	TL	146/143	G	1054	279	830	830	3000	2725
12R22.5	18PR	24.0	9.00	TL	152/149	L	1085	300	900	900	3550	3250
295/80R22.5	18PR	21.0	9.00	TL	152/149	L	1044	298	900	900	3550	3250
315/80R22.5	22PR	25.0	9.00	TL	167/164	D	1100	312	950	950	5450	5000

Performance Description:

⚠ Only fit for tractor and trailer

- Applied for short-haul, low speed and heavy loaded
- Special tread compound with high wear-resistance, suitable for mining application and construction sites.
- Aggressive lug pattern design provides excellent grip and traction performance.



HK863



Tyre Size	Ply Rating	Tread Depth (mm)	Standard Rim	Tube Type	Load Index	Speed Symbol	Overall Diameter (mm)	Section Width (mm)	Inflation Pressure(kpa)		Load Capacity(kg)	
									Single	Dual	Single	Dual
11R22.5	16PR	15.0	8.25	TL	146/143	M	1054	279	830	830	3000	2725
12R22.5	18PR	15.0	9.00	TL	152/148	L	1095	300	850	850	3550	3150

Performance Description:

⚠ Only fit for tractor and trailer

- Mixed highway and freeway for long distance and national transportation service, high speed.
- Special tread compound offers excellent performance of lower heat build-up and cut resistance,
- super grip on wet road and improved riding comfort.



HK870



Tyre Size	Ply Rating	Tread Depth (mm)	Standard Rim	Tube Type	Load Index	Speed Symbol	Overall Diameter (mm)	Section Width (mm)	Inflation Pressure(kpa)		Load Capacity(kg)	
									Single	Dual	Single	Dual
12R22.5	18PR	21.0	9.00	TL	152/149	L	1085	300	930	930	3550	3250
315/80R22.5	20PR	22.0	9.00	TL	156/150	L	1076	312	850	850	4000	3650

Performance Description:

⚠ Only fit for tractor and trailer

- Applied for national highway, standard highway with normal condition.
- Driving wheel, Good traction, braking and sideslip resistance.
- Extra deep tread provides excellent grip and driving capacity and also enhance tyre safety and abrasion resistance performance.



HK886



Tyre Size	Ply Rating	Tread Depth (mm)	Standard Rim	Tube Type	Load Index	Speed Symbol	Overall Diameter (mm)	Section Width (mm)	Inflation Pressure(kpa)		Load Capacity(kg)	
									Single	Dual	Single	Dual
12R22.5	18PR	18.0	9.00	TL	152/149	L	1085	300	930	930	3550	3250

Performance Description:

⚠ Only fit for tractor and trailer

- Three ribs ensure even wear and comfortable riding.
- Sipped zig-zag rib helps improve traction on wet and muddy surface.
- Deep circumferential grooves improve efficient water evacuation, lateral stability, and long tyre life.



HK893



Tyre Size	Ply Rating	Tread Depth (mm)	Standard Rim	Tube Type	Load Index	Speed Symbol	Overall Diameter (mm)	Section Width (mm)	Inflation Pressure(kpa)		Load Capacity(kg)	
									Single	Dual	Single	Dual
12.00R20	20PR	24.0	8.50	TT	156/153	B	1125	315	900	900	4000	3650

Performance Description:

⚠ Off the road/Only fit for Mine truck

- Applicable for driving wheels, for short distance with low speed on mining and bad roads.
- Pattern design offers excellent pulling force.
- Special tread compound offers excellent cut resistance.
- Reinforced bead design provides excellent load capacity.



HK896



Tyre Size	Ply Rating	Tread Depth (mm)	Standard Rim	Tube Type	Load Index	Speed Symbol	Overall Diameter (mm)	Section Width (mm)	Inflation Pressure(kpa)	Load Capacity(kg)
12R22.5	18PR	16.0	9.00	TL	152/149	L	1085	300	930 930	3550 3150

Performance Description:

⚠ Only fit for tractor and trailer

- Designed for highway transportation with good road conditions.
- Unique tread compound design with low rolling resistance,low heat build-up and minimized gasoline consumption.
- Enhanced channel sniping and wide grooves allow for premium wet and dry traction.



HLS6



Tyre Size	Ply Rating	Tread Depth (mm)	Standard Rim	Tube Type	Load Index	Speed Symbol	Overall Diameter (mm)	Section Width (mm)	Inflation Pressure(kpa)	Load Capacity(kg)
12R22.5	18PR	16.0	9.00	TL	152/149	L	1085	300	930 930	3550 3150

Performance Description:

⚠ Only fit for tractor and trailer

- Designed for highway transportation with good road conditions.
- Unique tread compound design with low rolling resistance,low heat build-up and minimized gasoline consumption.
- Enhanced channel sniping and wide grooves allow for premium wet and dry traction.



HRA2



Tyre Size	Ply Rating	Tread Depth (mm)	Standard Rim	Tube Type	Load Index	Speed Symbol	Overall Diameter (mm)	Section Width (mm)	Inflation Pressure(kpa)	Load Capacity(kg)
11.00R20	18PR	19.0	8.00	TT	152/149	K	1096	293	930 930	3550 3250

Performance Description:

⚠ Only fit for tractor and trailer

- Special tread compound and design enable low heat build-up,excellent puncture and cut resistance and minimized gasoline consumption.
- Super steel belt carcass construction enhances casing strength and maximizes tyre load capacity.
- Four ribs with transverse deep grooves optimize speed and traction performance, provides excellent performance on wet road surface.

SPEED SYMBOL

The SPEED SYMBOL indicates the speed at which the tire can carry a load corresponding to its load index service conditions specified by HAWKWAY.

Speed Symbol	Speed(km/h)	Speed Symbol	Speed(km/h)
B	50	M	130
C	60	N	140
D	65	P	150
E	70	Q	160
F	80	R	170
G	90	S	180
J	100	T	190
K	110	U	200
L	120	H	210