

MARVEMAX[®]



NEW OCEAN TRADING COMPANY LIMITED

Thuong Khuong, Vinh Hung commune,
Binh Giang district, Hai Duong province, Vietnam.
Tel: (+84) 098-307-1240
Email: congtydaiduongmoi@gmail.com

Manufactory official website: www.qingdaohawkyre.com
Website for global market: www.marvemaxyre.com

**PRODUCT
BROCHURE**

**RPIME TRACTOR &
SEMI TRAILER TYRE**



PRODUCT CATEGORIES

STEER

TRAILER

DRIVE

ALL POSITION



P03

MX920



P03

MX921



P04

MX927



P04

MX906



P05

MX922



P05

MX908



P06

MX910



P06

MX911



P07

MX925



P07

MX952



P08

MX959



P08

MX968



P09

MX969



P09

MX970



P10

MX993



P10

MX992



P10

MX096



P11

MX098



P11

MX901



P12

MX902



P12

MX986

SIZE	PATTERN								
11R22.5	MX902	MX921	MX959	MX969					
11R24.5	MX921	MX969							
12R22.5	MX901	MX902	MX910	MX920	MX927	MX968	MX970	MX986	MX992
13R22.5	MX902	MX911	MX959						
295/75R22.5	MX921	MX969							
295/80R22.5	MX902	MX921	MX927	MX968	MX970				
315/80R22.5	MX902	MX902+	MX921	MX927	MX968	MX970			
385/65R22.5	MX906	MX922							
11.00R20	MX901	MX902	MX908	MX920	MX925	MX952	MX993		
12.00R20	MX901	MX902	MX908	MX911	MX925	MX952	MX993		
12.00R24	MX902	MX096	MX098						

MARVEMAX[®] HIGH COST-EFFECTIVE TIRES




Only fit for Prime tractor & Semi trailer

PERFORMANCE DESCRIPTION:

- Medium and long distance,high speed on well paved road.
- Four straight-line and wave pattern around the bottom groove improved the handling performance.
- Low-heat generation,low noise,low-rolling resistance.

MX920



SIZE	PLY RATING	TREAD DEPTH (MM)	STANDARD RIM	TUBE TYPE	LOAD INDEX	SPEED SYMBOL	OVERALL DIAMETER (MM)	SECTION WIDTH (MM)	INFLATION PRESSURE (KPA)	MAX LOAD(KG) (SINGLE/DUAL)
12R22.5	18PR	15.0	9.00	TL	152/149	M	1084	300	930	3550/3250
11.00R20	18PR	17.0	8.00	TT	152/149	L	1085	293	930	3550/3250




Only fit for Prime tractor & Semi trailer

PERFORMANCE DESCRIPTION:

- Medium and long distance ,high speed on well paved road.
- Four straight-line and wave pattern around the bottom groove improved the handling performance.
- Low-heat generation,low nosie,low-rolling resistance.

MX927



SIZE	PLY RATING	TREAD DEPTH (MM)	STANDARD RIM	TUBE TYPE	LOAD INDEX	SPEED SYMBOL	OVERALL DIAMETER (MM)	SECTION WIDTH (MM)	INFLATION PRESSURE (KPA)	MAX LOAD(KG) (SINGLE/DUAL)
12R22.5	18PR	15.0	9.00	TL	152/149	M	1084	300	930	3550/3250
295/80R22.5	18PR	14.0	9.00	TL	152/149	M	1044	298	900	3550/3250
315/80R22.5	20PR	14.5	9.00	TL	156/150	M	1076	312	850	4000/3350




Only fit for Prime tractor & Semi trailer

PERFORMANCE DESCRIPTION:

- Suitable for short/middle distance,running on mixed pavements and secondary road.
- Large-scale and longitudinal groove mixed pattern,excellent driving force and braking force.
- Wide driving surface design,longer wear life.

MX921



SIZE	PLY RATING	TREAD DEPTH (MM)	STANDARD RIM	TUBE TYPE	LOAD INDEX	SPEED SYMBOL	OVERALL DIAMETER (MM)	SECTION WIDTH (MM)	INFLATION PRESSURE (KPA)	MAX LOAD(KG) (SINGLE/DUAL)
11R24.5	18PR	14.0	8.25	TL	152/149	M	1104	279	830	3250/3000
11R22.5	18PR	14.5	8.25	TL	149/146	M	1054	279	830	3000/2725
295/75R22.5	16PR	14.0	9.00	TL	146/143	L	1014	298	830	3000/2725
295/80R22.5	18PR	14.5	9.00	TL	152/149	M	1044	298	900	3550/3250
315/80R22.5	20PR	14.5	9.00	TL	156/150	M	1076	312	850	4000/3350




Only fit for Prime tractor & Semi trailer

PERFORMANCE DESCRIPTION:

- All positions,fit for medium,long distance and high speed driving on well paved road.
- High speed performance and good driveability.
- Low-heat generation,low noise emission,good grip performance.

MX906



SIZE	PLY RATING	TREAD DEPTH (MM)	STANDARD RIM	TUBE TYPE	LOAD INDEX	SPEED SYMBOL	OVERALL DIAMETER (MM)	SECTION WIDTH (MM)	INFLATION PRESSURE (KPA)	MAX LOAD(KG) (SINGLE/DUAL)
385/65R22.5	20PR	14.5	11.75	TL	160	K	1072	288	900	4500/--

MARVEMAX[®] HIGH COST-EFFECTIVE TIRES

TRAILER / DRIVE




Only fit for Prime tractor & Semi trailer

PERFORMANCE DESCRIPTION:

- Suitable for short/middle distance, running on mixed pavements and secondary road.
- Large-scale and longitudinal groove mixed pattern, excellent driving force and braking force.
- Wide driving surface design, longer wear life.

TRAILER

MX922



SIZE	PLY RATING	TREAD DEPTH (MM)	STANDARD RIM	TUBE TYPE	LOAD INDEX	SPEED SYMBOL	OVERALL DIAMETER (MM)	SECTION WIDTH (MM)	INFLATION PRESSURE (KPA)	MAX LOAD (KG) [SINGLE/DUAL]
385/65R22.5	20PR	14.5	11.75	TL	160	K	1072	288	900	4500/--



Only fit for Prime tractor & Semi trailer

PERFORMANCE DESCRIPTION:

- Applied for low speed, mining, gravel etc, bad road conditions, all position of trucks.
- Deepened pattern and simple big block design, special tread compound providing outstanding anti pricking and anti chunking ability.
- Excellent driving force and braking force. Good grip performance on all kinds of complex roads.

DRIVE

MX910



SIZE	PLY RATING	TREAD DEPTH (MM)	STANDARD RIM	TUBE TYPE	LOAD INDEX	SPEED SYMBOL	OVERALL DIAMETER (MM)	SECTION WIDTH (MM)	INFLATION PRESSURE (KPA)	MAX LOAD (KG) [SINGLE/DUAL]
12R22.5	18PR	23.0	9.00	TL	152/149	L	1096	300	930	3550/3250



Only fit for Prime tractor & Semi trailer

PERFORMANCE DESCRIPTION:

- Applied for low speed, mining, gravel etc, bad road conditions, all position of trucks.
- Deepened pattern and simple big block design, special tread compound providing outstanding anti pricking and anti chunking ability.
- Excellent driving force and braking force. Good grip performance on all kinds of complex roads.

DRIVE

MX908



SIZE	PLY RATING	TREAD DEPTH (MM)	STANDARD RIM	TUBE TYPE	LOAD INDEX	SPEED SYMBOL	OVERALL DIAMETER (MM)	SECTION WIDTH (MM)	INFLATION PRESSURE (KPA)	MAX LOAD (KG) [SINGLE/DUAL]
11.00R20	18PR	23.0	8.00	TT	152/149	F	1085	293	930	3550/3250
12.00R20	20PR	23.5	8.50	TT	156/153	F	1135	315	900	4000/3650




Only fit for Prime tractor & Semi trailer

PERFORMANCE DESCRIPTION:

- Suitable for short/middle distance, running on mixed pavements and secondary road.
- Large-scale and longitudinal groove mixed pattern, excellent driving force and braking force.
- Wide driving surface design, longer wear life.

DRIVE

MX911



SIZE	PLY RATING	TREAD DEPTH (MM)	STANDARD RIM	TUBE TYPE	LOAD INDEX	SPEED SYMBOL	OVERALL DIAMETER (MM)	SECTION WIDTH (MM)	INFLATION PRESSURE (KPA)	MAX LOAD (KG) [SINGLE/DUAL]
12.00R20	20PR	18.5	8.50	TT	156/153	L	1125	315	900	4000/3650
13R22.5	20PR	21.0	9.75	TL	154/151	L	1124	320	875	4000/3350

MARVEMAX[®] HIGH COST-EFFECTIVE TIRES




Only fit for Prime tractor & Semi trailer

PERFORMANCE DESCRIPTION:

- For driving on mixed road ,low speed ,short distance.
- Large pattern with stiffener and staggered pattern design provides good driving and braking performance.
- Deep pattern design for longer lifetime.

DRIVE

MX925



SIZE	PLY RATING	TREAD DEPTH (MM)	STANDARD RIM	TUBE TYPE	LOAD INDEX	SPEED SYMBOL	OVERALL DIAMETER (MM)	SECTION WIDTH (MM)	INFLATION PRESSURE (KPA)	MAX LOAD(KG) [SINGLE/DUAL]
11.00R20	18PR	17.5	8.00	TT	152/149	L	1085	293	930	3550/3250
12.00R20	20PR	18.5	8.50	TT	156/153	L	1125	315	900	4000/3650




Only fit for Prime tractor & Semi trailer

PERFORMANCE DESCRIPTION:

- Suitable for short/middle distance,running on mixed pavements and secondary road.
- Large-scale and longitudinal groove mixed pattern,excellent driving force and braking force.
- Wide driving surface design,longer wear life.

DRIVE

MX959



SIZE	PLY RATING	TREAD DEPTH (MM)	STANDARD RIM	TUBE TYPE	LOAD INDEX	SPEED SYMBOL	OVERALL DIAMETER (MM)	SECTION WIDTH (MM)	INFLATION PRESSURE (KPA)	MAX LOAD(KG) [SINGLE/DUAL]
11R22.5	18PR	18.5	8.25	TL	149/146	L	1065	279	830	3250/3000
13R22.5	20PR	18.5	9.75	TL	154/151	L	1124	235	830	3750/3450



Only fit for Prime tractor & Semi trailer

PERFORMANCE DESCRIPTION:

- Suitable for short/middle distance,running on mixed pavements and secondary road.
- Large-scale and longititudianl groove mixed pattern,excellent driving force and braking force.
- Strong durability and overload performance.

DRIVE

MX952



SIZE	PLY RATING	TREAD DEPTH (MM)	STANDARD RIM	TUBE TYPE	LOAD INDEX	SPEED SYMBOL	OVERALL DIAMETER (MM)	SECTION WIDTH (MM)	INFLATION PRESSURE (KPA)	MAX LOAD(KG) [SINGLE/DUAL]
11.00R20	18PR	17.5	8.00	TT	152/149	L	1085	293	930	3550/3250
12.00R20	20PR	18.5	8.50	TT	156/153	L	1125	315	900	4000/3650



Only fit for Prime tractor & Semi trailer

PERFORMANCE DESCRIPTION:

- Suitable for short/middle distance,running on mixed pavements and secondary road.
- Large-scale and longitudinal groove mixed pattern,excellent driving force and braking force.
- Wide driving surface design,longer wear life.

DRIVE

MX968



SIZE	PLY RATING	TREAD DEPTH (MM)	STANDARD RIM	TUBE TYPE	LOAD INDEX	SPEED SYMBOL	OVERALL DIAMETER (MM)	SECTION WIDTH (MM)	INFLATION PRESSURE (KPA)	MAX LOAD(KG) [SINGLE/DUAL]
12R22.5	18PR	19.0	9.00	TL	152/149	L	1094	300	930	3550/3250
295/80R22.5	18PR	19.5	9.00	TL	152/149	L	1044	298	900	3550/3250
315/80R22.5	20PR	19.0	9.00	TL	156/150	L	1076	312	850	4000/3350

MARVEMAX[®] HIGH COST-EFFECTIVE TIRES

DRIVE / ALL POSITION




Only fit for Prime tractor & Semi trailer

PERFORMANCE DESCRIPTION:

- Medium and long distance ,high speed on well paved road.
- The middle block design and the shoulder closed design ensure the grip of the tire and reduce the rolling resistance of the tire.
- Special block pattern design ,with higher driving force,excellent ground rolling resistance performance.

DRIVE



MX969

SIZE	PLY RATING	TREAD DEPTH (MM)	STANDARD RIM	TUBE TYPE	LOAD INDEX	SPEED SYMBOL	OVERALL DIAMETER (MM)	SECTION WIDTH (MM)	INFLATION PRESSURE (KPA)	MAX LOAD(KG) [SINGLE/DUAL]
11R22.5	18PR	19.5	8.25	TL	149/146	L	1065	279	930	3250/3000
11R24.5	18PR	19.5	8.25	TL	152/149	L	1116	279	830	3250/3000
295/75R22.5	16PR	19.5	9.00	TL	146/143	L	1014	298	830	3000/2725



Only fit for Prime tractor & Semi trailer

PERFORMANCE DESCRIPTION:

- Applied for low speed,mining,gravel etc,bad road conditions,all position of trucks.
- Optimize the layout design of pattern block and groove angle provides excellent traction performance.
- The design of tear resistant tread formula makes,its tread lift more tear resistant.

DRIVE



MX993

SIZE	PLY RATING	TREAD DEPTH (MM)	STANDARD RIM	TUBE TYPE	LOAD INDEX	SPEED SYMBOL	OVERALL DIAMETER (MM)	SECTION WIDTH (MM)	INFLATION PRESSURE (KPA)	MAX LOAD(KG) [SINGLE/DUAL]
11.00R20	18PR	23.0	8.00	TT	152/149	F	1095	293	930	3550/3250
12.00R20	20PR	23.5	8.50	TT	156/153	F	1135	315	900	4000/3650




Only fit for Prime tractor & Semi trailer

PERFORMANCE DESCRIPTION:

- Mainly applicable to the drive shaft of vehicles with fixed load,long distance and high speed driving on good pavement.
- Deep groove and wide driving surface design,with superior high wear life.
- Special block pattern design,with higher braking and driving.

DRIVE



MX970

SIZE	PLY RATING	TREAD DEPTH (MM)	STANDARD RIM	TUBE TYPE	LOAD INDEX	SPEED SYMBOL	OVERALL DIAMETER (MM)	SECTION WIDTH (MM)	INFLATION PRESSURE (KPA)	MAX LOAD(KG) [SINGLE/DUAL]
12R22.5	18PR	19.0	9.00	TL	152/149	L	1085	300	900	3550/3250
295/80R22.5	18PR	19.5	9.00	TL	152/149	L	1044	298	900	3550/3250
315/80R22.5	20PR	19.0	9.00	TL	156/150	L	1082	312	850	4000/3350




Only fit for Prime tractor & Semi trailer

PERFORMANCE DESCRIPTION:

- All positions,fit for medium and long distance,high speed on well paved road.
- Zigzag groove and shoulder groove design,excellent drive performance handling performance.
- Widened running surface and optimized grounding pressure,outstanding wear resistance.

ALL POSITION



MX096

SIZE	PLY RATING	TREAD DEPTH (MM)	STANDARD RIM	TUBE TYPE	LOAD INDEX	SPEED SYMBOL	OVERALL DIAMETER (MM)	SECTION WIDTH (MM)	INFLATION PRESSURE (KPA)	MAX LOAD(KG) [SINGLE/DUAL]
12.00R24	20PR	14.5	8.50	TT	160/157	K	1226	315	900	4500/4125

MARVEMAX[®] HIGH COST-EFFECTIVE TIRES




Only fit for Prime tractor & Semi trailer

PERFORMANCE DESCRIPTION:

- All positions, fit for medium and long distance, high speed on well paved road.
- Excellent drive performance and handling performance.
- Widened running surface and optimized grounding pressure, outstanding wear resistance.

ALL POSITION



MX098

SIZE	PLY RATING	TREAD DEPTH (MM)	STANDARD RIM	TUBE TYPE	LOAD INDEX	SPEED SYMBOL	OVERALL DIAMETER (MM)	SECTION WIDTH (MM)	INFLATION PRESSURE (KPA)	MAX LOAD (KG) [SINGLE/DUAL]
12.00R24	20PR	14.5	8.50	TT	160/157	K	1226	315	900	4500/4125




Only fit for Prime tractor & Semi trailer

PERFORMANCE DESCRIPTION:

- All position, applied for highway, urban and country road.
- Three rib pattern, extra sideslip resistance, delivers superior stability and drainage of driving.

ALL POSITION



MX901

SIZE	PLY RATING	TREAD DEPTH (MM)	STANDARD RIM	TUBE TYPE	LOAD INDEX	SPEED SYMBOL	OVERALL DIAMETER (MM)	SECTION WIDTH (MM)	INFLATION PRESSURE (KPA)	MAX LOAD (KG) [SINGLE/DUAL]
11.00R20	18PR	17.0	8.00	TT	152/149	L	1085	293	930	3550/3250
12.00R20	20PR	16.0	8.50	TT	156/153	L	1125	315	900	4000/3650
12R22.5	18PR	15.0	9.00	TL	152/149	M	1085	300	930	3550/3250




Only fit for Prime tractor & Semi trailer

PERFORMANCE DESCRIPTION:

- All positions, fit for driving on various roads.
- Mature pattern design, superior traction performance, braking performance and wet sliding resistance.
- High efficiency of heat dissipation and strong driving force due to large tread groove on shoulder.

ALL POSITION



MX902 /MX902+

SIZE	PLY RATING	TREAD DEPTH (MM)	STANDARD RIM	TUBE TYPE	LOAD INDEX	SPEED SYMBOL	OVERALL DIAMETER (MM)	SECTION WIDTH (MM)	INFLATION PRESSURE (KPA)	MAX LOAD (KG) [SINGLE/DUAL]
11.00R20	18PR	17.0	8.00	TT	152/149	L	1085	293	930	3550/3250
12.00R20	20PR	16.0	8.50	TT	156/153	L	1125	315	900	4000/3650
12.00R24	20PR	14.5	8.50	TT	160/157	K	1226	315	900	4500/4125
11R22.5	18PR	14.5	8.25	TL	149/146	M	1054	279	830	3000/2725
12R22.5	18PR	15.0	9.00	TL	152/149	M	1085	300	930	3550/3250
13R22.5	20PR	16.0	9.75	TL	154/151	M	1124	320	830	3750/3450
295/80R22.5	18PR	14.0	9.00	TL	152/149	M	1044	298	900	3550/3250
☆ 315/80R22.5	20PR	14.5	9.00	TL	156/150	M	1076	312	850	4000/3350




Only fit for Prime tractor & Semi trailer

PERFORMANCE DESCRIPTION:

- All positions, fit for medium and long distance, high speed on well paved road.
- Excellent drive performance and handling performance.
- Widened running surface and optimized grounding pressure, outstanding wear resistance.

ALL POSITION



MX986

SIZE	PLY RATING	TREAD DEPTH (MM)	STANDARD RIM	TUBE TYPE	LOAD INDEX	SPEED SYMBOL	OVERALL DIAMETER (MM)	SECTION WIDTH (MM)	INFLATION PRESSURE (KPA)	MAX LOAD (KG) [SINGLE/DUAL]
12R22.5	18PR	15.0	9.00	TL	152/149	M	1085	300	930	3550/3250

SPEED SYMBOL

LOAD CAPACITY INDEX

Speed Symbol	Speed(km/h)	Speed Symbol	Speed(km/h)
B	50	M	130
C	60	N	140
D	65	P	150
E	70	Q	160
F	80	R	170
G	90	S	180
J	100	T	190
K	110	U	200
L	120	H	210

LI	KG	LI	KG	LI	KG
115	1215	136	2240	157	4125
116	1250	137	2300	158	4250
117	1285	138	2360	159	4375
118	1320	139	2430	160	4500
119	1360	140	2500	161	4625
120	1400	141	2575	162	4750
121	1450	142	2650	163	4875
122	1500	143	2725	164	5000
123	1550	144	2800	165	5150
124	1600	145	2900	166	5300
125	1650	146	3000	167	5450
126	1700	147	3075	168	5600
127	1750	148	3150	169	5800
128	1800	149	3250	170	6000
129	1850	150	3350	171	6150
130	1900	151	3450	172	6300
131	1950	152	3550	173	6500
132	2000	153	3650	174	6700
133	2060	154	3750	175	6900
134	2120	155	3875	176	7100
135	2180	156	4000	177	7300



ⓘ Off the road/Only fit for Mine truck

PERFORMANCE DESCRIPTION:

- Applied for low speed,mining,gravel etc,bad road conditions,all position of trucks.
- Deepened pattern and simple big block design,special tread compound providing outstanding anti pricking and anti chunking ability.
- Excellent driving force and braking force.Good grip performance on all kinds of complex roads.

MX992



SIZE	PLY RATING	TREAD DEPTH (MM)	STANDARD RIM	TUBE TYPE	LOAD INDEX	SPEED SYMBOL	OVERALL DIAMETER (MM)	SECTION WIDTH (MM)	INFLATION PRESSURE (KPA)	MAX LOAD(KG) [SINGLE/DUAL]
12R22.5	18PR	24.0	9.00	TL	152/149	A8	1096	300	930	3550/3250