



For more information pls contact :

NEW OCEAN TRADING COMPANY LIMITED

Thuong Khuong, Vinh Hung commune, Binh
Giang district, Hai Duong province, Vietnam

Tel: (+84) 098-307-1240

Email: congtydaiduongmoi@gmail.com

www.qingdaohawktyre.com



**PREMIUM TYRE
MANUFACTURER**
SINCE 1975



Introduction

Hawk Tyre International Ltd , a global tire supplier integrating tire research and development, production and marketing,now mainly deals with four segments including primer tractor and trailer tires, mining tires, OTR tires,agricultural tires and industrial tires. Relying on over 40 years of tire manufacturing experience and market accumulation, Hawk Tyre products feature high loading capacity,super wear-resistance,and great adaptation to complex road conditions. Credited with ISO9001, CCC, DOT, ECE, SMARTWAY, GCC, SNI and other international certifications, the company's brands "HAWKWAY" "SUPERHAWK" "YINGBA" "MARVEMAX" are distributed to more than 80 countries in Southeast Asia, America, Australia and Africa etc, and all received with positive feedback by global partners.

Look forward to the future, Hawk Tyre will continue toimprove the user experience towards the product and focus onproviding all partners with full range customized servicesincluding professional pre-sales training,trackingguidance and advertisement support, after-salesassistance to solve problems. To achieve customer’ssatisfaction is our pursuit.



SIZE	PATTERN								
11.00R20	YB602	YB607+	YB610	YB628	YB632+	YB650+			
12.00R20	YB602	YB607+	YB610	YB628	YB632+	YB650+	YB691	YB692+	
12R22.5	YB602	YB623	YB625	YB630	YB655	YB670	YB682		
12.00R24	YB607+								
315/80R22.5	YLS1								

YB602



Performance Description:

- Applied for express way and urban road, all position
- Rib pattern, extra sideslip resistance, pitch pattern designed,low noise.
- By four staight main slots and it delivers superior stability and drainage of driving.
- Super steel belt carcass construction enhances casing strength and maximizes tire load capacity.

Only fit for tractor and trailer

TYRE SIZE	PLY RATING	TREAD DEPTH (mm)	STANDARD RIM	TUBE TYPE	LOAD INDEX	SPEED SYMBOL	OVERALL DIAMETER (mm)	SECTION WIDTH (mm)	INFLATION PRESSURE (kpa)		LOAD CAPACITY (kg)	
									SINGLE	DUAL	SINGLE	DUAL
12.00R20	20PR	17.0	8.50	TT	156/153	K	1125	315	930	930	4000	3650
12R22.5	18PR	17.0	9.00	TL	152/149	L	1085	300	930	930	3550	3250

YLS1



Performance Description:

- Super Wide and Extremely wear-resistant.
- Mixed highway and freeway for long distance and national transportation service.
- Contact Area 10% bigger than regular design.
- Larger footprint for drive comfort and long tread wear.
- Enhanced channel siping and wide grooves allow for premium wet and dry traction.

Only fit for tractor and trailer

TYRE SIZE	PLY RATING	TREAD DEPTH (mm)	STANDARD RIM	TUBE TYPE	LOAD INDEX	SPEED SYMBOL	OVERALL DIAMETER (mm)	SECTION WIDTH (mm)	INFLATION PRESSURE (kpa)		LOAD CAPACITY (kg)	
									SINGLE	DUAL	SINGLE	DUAL
315/80R22.5	18PR	16.0	9.00	TL	156/150	L	1096	318	850	850	4000	3550



YB607+



• **Performance Description:**

- Super Wide and Extremely wear-resistant.
- Applied for short-haul , low speed, and heavy loaded mine trucks.
- Excellent stab-resistance, anti-eccentric worn, avulsion resistance and tread wear ability.
- Aggressive lug pattern design provides excellent grip and traction performance.

❗ Off the road/Only fit for Mine truck

TYRE SIZE	PLY RATING	TREAD DEPTH (mm)	STANDARD RIM	TUBE TYPE	LOAD INDEX	SPEED SYMBOL	OVERALL DIAMETER (mm)	SECTION WIDTH (mm)	INFLATION PRESSURE (kpa)		LOAD CAPACITY (kg)	
									SINGLE	DUAL	SINGLE	DUAL
11.00R20	18PR	25.0	8.00	TT	152/149	B	1085	295	930	930	3550	3250
12.00R20	20PR	25.0	8.50	TT	156/153	B	1125	315	900	900	4000	3650
12.00R20	22PR	25.0	8.50	TT	156/153	B	1125	315	900	900	4250	3875
12.00R24	24PR	25.0	8.50	TT	164/161	B	1226	315	900	900	5000	4625



YB610



• **Performance Description:**

- Applied for short-haul , low speed, and heavy loaded mine trucks.
- Special tread compound with high wear-resistance, suitable for mining application and construction sites.
- Aggressive lug pattern design provides excellent grip and traction performance.

❗ Off the road/Only fit for Mine truck

TYRE SIZE	PLY RATING	TREAD DEPTH (mm)	STANDARD RIM	TUBE TYPE	LOAD INDEX	SPEED SYMBOL	OVERALL DIAMETER (mm)	SECTION WIDTH (mm)	INFLATION PRESSURE (kpa)		LOAD CAPACITY (kg)	
									SINGLE	DUAL	SINGLE	DUAL
11.00R20	18PR	25.0	8.00	TT	152/149	B	1085	295	930	930	3550	3250
12.00R20	22PR	25.5	8.50	TT	158/155	B	1125	315	970	970	4250	3875



YB623



• **Performance Description:**

- The wide and flat tread provides excellent wear resistance.The deep pattern offers long serve life.
- For belts construction and closed shoulder resistant uneven wear.
- Strong carcass and belts provide more load capacity.

❗ Only fit for tractor and trailer

TYRE SIZE	PLY RATING	TREAD DEPTH (mm)	STANDARD RIM	TUBE TYPE	LOAD INDEX	SPEED SYMBOL	OVERALL DIAMETER (mm)	SECTION WIDTH (mm)	INFLATION PRESSURE (kpa)		LOAD CAPACITY (kg)	
									SINGLE	DUAL	SINGLE	DUAL
12R22.5	18PR	19.0	9.00	TL	152/149	L	1085	300	930	930	3550	3250



YB625



• **Performance Description:**

- Super wide and extremely wear-resistant.
- Special designed for long haul. Perform well on good road condistion high speed.
- Contact area 10% bigger than regular design.
- Larger footprint for drive comfort and long tread wear.
- Strong bead structure insures longer endurance and lifespan.

❗ Only fit for tractor and trailer

TYRE SIZE	PLY RATING	TREAD DEPTH (mm)	STANDARD RIM	TUBE TYPE	LOAD INDEX	SPEED SYMBOL	OVERALL DIAMETER (mm)	SECTION WIDTH (mm)	INFLATION PRESSURE (kpa)		LOAD CAPACITY (kg)	
									SINGLE	DUAL	SINGLE	DUAL
12R22.5	18PR	18.0	9.00	TL	152/149	L	1085	300	930	930	3550	3250



YB628



• **Performance Description:**

- Patented unique design for mixed road conditions,national and regional haul.
- Tread design makes it wear-resistant and anti-cut.
- Super steel belt carcass construction enhance casing strength and maximizes tire load capacity.

❗ Only fit for tractor and trailer

TYRE SIZE	PLY RATING	TREAD DEPTH (mm)	STANDARD RIM	TUBE TYPE	LOAD INDEX	SPEED SYMBOL	OVERALL DIAMETER (mm)	SECTION WIDTH (mm)	INFLATION PRESSURE (kpa)		LOAD CAPACITY (kg)	
									SINGLE	DUAL	SINGLE	DUAL
11.00R20	18PR	19.0	8.00	TT	152/149	K	1085	293	930	930	3550	3250
12.00R20	20PR	19.5	8.50	TT	156/153	K	1125	315	930	930	4000	3650



YB630G



• **Performance Description:**

- Super Wide and Extremely wear-resistant.
- Mixed highway and freeway for long distance and national transportation service.
- Contact Area 10% bigger than regular design.
- Larger footprint for drive comfort and long tread wear.
- Enhanced channel siping and wide grooves allow for premium wet and dry traction.

❗ Only fit for tractor and trailer

TYRE SIZE	PLY RATING	TREAD DEPTH (mm)	STANDARD RIM	TUBE TYPE	LOAD INDEX	SPEED SYMBOL	OVERALL DIAMETER (mm)	SECTION WIDTH (mm)	INFLATION PRESSURE (kpa)		LOAD CAPACITY (kg)	
									SINGLE	DUAL	SINGLE	DUAL
12R22.5	18PR	18.0	9.00	TL	152/149	L	1085	300	930	930	3550	3250





YB632/YB632+



• **Performance Description:**

- Super Wide and Extremely wear-resistant.
- Applied for short-haul , low speed, and heavy loaded.
- Special tread compound with high wear-resistant, suitable for mining application and construction sites.
- Aggressive block pattern design provides excellent grip and traction performance.



Only fit for tractor and trailer



TYRE SIZE	PLY RATING	TREAD DEPTH (mm)	STANDARD RIM	TUBE TYPE	LOAD INDEX	SPEED SYMBOL	OVERALL DIAMETER (mm)	SECTION WIDTH (mm)	INFLATION PRESSURE (kpa)		LOAD CAPACITY (kg)	
									SINGLE	DUAL	SINGLE	DUAL
11.00R20	18PR	18.0	8.00	TT	152/149	K	1085	293	930	930	3550	3250
12.00R20	20PR	19.0	8.50	TT	156/153	K	1125	315	900	900	4000	3650
12.00R20	22PR	19.0	8.50	TT	156/153	K	1125	315	900	900	4250	3875

YB650/YB650+



• **Performance Description:**

- Super Wide and Extremely wear-resistant.
- Applied for short-haul , low speed, and heavy loaded
- Special tread compound with high wear-resistant, suitable for mining application and construction sites.
- Aggressive block pattern design provides excellent grip and traction performance.



Only fit for tractor and trailer



TYRE SIZE	PLY RATING	TREAD DEPTH (mm)	STANDARD RIM	TUBE TYPE	LOAD INDEX	SPEED SYMBOL	OVERALL DIAMETER (mm)	SECTION WIDTH (mm)	INFLATION PRESSURE (kpa)		LOAD CAPACITY (kg)	
									SINGLE	DUAL	SINGLE	DUAL
11.00R20	18PR	19.0	8.00	TT	152/149	K	1085	293	930	930	3550	3250
12.00R20	20PR	20.0	8.50	TT	156/153	K	1125	315	900	900	4000	3650
12.00R20	22PR	20.0	8.50	TT	156/153	K	1125	315	900	900	4250	3875

YB670



• **Performance Description:**

- Applied for national highway, standard highway with normal condition.
- Driving wheel of long haul tractor,Good traction, braking and sideslip resistance.
- Extra deep tread provides excellent grip and driving capacity and also enhance tyre safty and abrasion resistance performance.



Only fit for tractor and trailer



TYRE SIZE	PLY RATING	TREAD DEPTH (mm)	STANDARD RIM	TUBE TYPE	LOAD INDEX	SPEED SYMBOL	OVERALL DIAMETER (mm)	SECTION WIDTH (mm)	INFLATION PRESSURE (kpa)		LOAD CAPACITY (kg)	
									SINGLE	DUAL	SINGLE	DUAL
12R22.5	18PR	21.0	9.00	TL	152/149	L	1085	300	930	930	3550	3250

YB682G



• **Performance Description:**

- Super wide and extremely wear-resistant.
- Special designed for long haul. Perform well on good road condistion high speed.
- Contact area 10% bigger than regular design.
- Larger footprint for drive comfort and long tread wear.
- Strong bead structure insures longer endurance and lifespan.



Only fit for tractor and trailer



TYRE SIZE	PLY RATING	TREAD DEPTH (mm)	STANDARD RIM	TUBE TYPE	LOAD INDEX	SPEED SYMBOL	OVERALL DIAMETER (mm)	SECTION WIDTH (mm)	INFLATION PRESSURE (kpa)		LOAD CAPACITY (kg)	
									SINGLE	DUAL	SINGLE	DUAL
12R22.5	18PR	19.0	9.00	TL	152/149	L	1085	300	930	930	3550	3250

YB691



Performance Description:

- Applicable for driving wheels.
- For short distance with low speed on mining and bad roads.
- Pattern design offers excellent pulling force.
- Special tread compound offers excellent cut resistance.
- Reinforced bead design provides excellent load capacity.



Off the road/Only fit for Mine truck



TYRE SIZE	PLY RATING	TREAD DEPTH (mm)	STANDARD RIM	TUBE TYPE	LOAD INDEX	SPEED SYMBOL	OVERALL DIAMETER (mm)	SECTION WIDTH (mm)	INFLATION PRESSURE (kpa)		LOAD CAPACITY (kg)	
									SINGLE	DUAL	SINGLE	DUAL
12.00R20	20PR	26.0	8.50	TT	156/153	B	1125	315	900	900	4000	3650
12.00R20	22PR	26.0	8.50	TT	156/153	B	1125	315	900	900	4250	3875

YB692+



• **Performance Description:**

- Applicable for driving wheels.For short distance with low speed on mining and bad roads.
- Pattern design offers excellent pulling force.
- Special tread compound offers excellent cut resistance.
- Reinforced bead design provides excellent load capacity.



Off the road/Only fit for Mine truck



TYRE SIZE	PLY RATING	TREAD DEPTH (mm)	STANDARD RIM	TUBE TYPE	LOAD INDEX	SPEED SYMBOL	OVERALL DIAMETER (mm)	SECTION WIDTH (mm)	INFLATION PRESSURE (kpa)		LOAD CAPACITY (kg)	
									SINGLE	DUAL	SINGLE	DUAL
11.00R20	18PR	25.0	8.00	TT	156/153	B	1085	295	930	930	3550	3250
12.00R20	20PR	25.0	8.50	TT	152/149	B	1125	315	900	900	4000	3650