

**MARVEMAX<sup>®</sup>**



**NEW OCEAN TRADING COMPANY LIMITED**

Thuong Khuong, Vinh Hung commune,  
Binh Giang district, Hai Duong province, Vietnam.  
Tel: (+84) 098-307-1240  
Email: congtydaiduongmoi@gmail.com

Manufactory official website: [www.qingdaohawkyre.com](http://www.qingdaohawkyre.com)  
Website for global market: [www.marvemaxyre.com](http://www.marvemaxyre.com)

**PRODUCT  
BROCHURE**

**PRIME TRACTOR &  
SEMI TRAILER TYRE**





# PRODUCT CATEGORIES

STEER



P03

P03

P04

MX920

MX921

MX927

TRAILER



P04

P05

MX906

MX922

DRIVE



P05

P06

P06

P07

P07

P08

MX908

MX910

MX911

MX925

MX952

MX959



P08

P09

P09

P10

MX968

MX969

MX970

MX993

MX992

ALL POSITION



P10

P11

P11

P12

P12

MX096

MX098

MX901

MX902

MX986

| SIZE        | PATTERN |        |       |       |       |       |       |       |       |
|-------------|---------|--------|-------|-------|-------|-------|-------|-------|-------|
| 11R22.5     | MX902   | MX921  | MX959 | MX969 |       |       |       |       |       |
| 11R24.5     | MX921   | MX969  |       |       |       |       |       |       |       |
| 12R22.5     | MX901   | MX902  | MX910 | MX920 | MX927 | MX968 | MX970 | MX986 | MX992 |
| 13R22.5     | MX902   | MX911  | MX959 |       |       |       |       |       |       |
| 295/75R22.5 | MX921   | MX969  |       |       |       |       |       |       |       |
| 295/80R22.5 | MX902   | MX921  | MX927 | MX968 | MX970 |       |       |       |       |
| 315/80R22.5 | MX902   | MX902+ | MX921 | MX927 | MX968 | MX970 |       |       |       |
| 385/65R22.5 | MX906   | MX922  |       |       |       |       |       |       |       |
| 11.00R20    | MX901   | MX902  | MX908 | MX920 | MX925 | MX952 | MX993 |       |       |
| 12.00R20    | MX901   | MX902  | MX908 | MX911 | MX925 | MX952 | MX993 |       |       |
| 12.00R24    | MX902   | MX096  | MX098 |       |       |       |       |       |       |



# MARVEMAX<sup>®</sup> HIGH COST-EFFECTIVE TIRES




Only fit for Prime tractor & Semi trailer

### PERFORMANCE DESCRIPTION:

- Medium and long distance,high speed on well paved road.
- Four straight-line and wave pattern around the bottom groove improved the handling performance.
- Low-heat generation,low noise,low-rolling resistance.

## MX920



| SIZE     | PLY RATING | TREAD DEPTH (MM) | STANDARD RIM | TUBE TYPE | LOAD INDEX | SPEED SYMBOL | OVERALL DIAMETER (MM) | SECTION WIDTH (MM) | INFLATION PRESSURE (KPA) | MAX LOAD(KG) (SINGLE/DUAL) |
|----------|------------|------------------|--------------|-----------|------------|--------------|-----------------------|--------------------|--------------------------|----------------------------|
| 12R22.5  | 18PR       | 15.0             | 9.00         | TL        | 152/149    | M            | 1084                  | 300                | 930                      | 3550/3250                  |
| 11.00R20 | 18PR       | 17.0             | 8.00         | TT        | 152/149    | L            | 1085                  | 293                | 930                      | 3550/3250                  |




Only fit for Prime tractor & Semi trailer

### PERFORMANCE DESCRIPTION:

- Medium and long distance ,high speed on well paved road.
- Four straight-line and wave pattern around the bottom groove improved the handling performance.
- Low-heat generation,low nosie,low-rolling resistance.

## MX927



| SIZE        | PLY RATING | TREAD DEPTH (MM) | STANDARD RIM | TUBE TYPE | LOAD INDEX | SPEED SYMBOL | OVERALL DIAMETER (MM) | SECTION WIDTH (MM) | INFLATION PRESSURE (KPA) | MAX LOAD(KG) (SINGLE/DUAL) |
|-------------|------------|------------------|--------------|-----------|------------|--------------|-----------------------|--------------------|--------------------------|----------------------------|
| 12R22.5     | 18PR       | 15.0             | 9.00         | TL        | 152/149    | M            | 1084                  | 300                | 930                      | 3550/3250                  |
| 295/80R22.5 | 18PR       | 14.0             | 9.00         | TL        | 152/149    | M            | 1044                  | 298                | 900                      | 3550/3250                  |
| 315/80R22.5 | 20PR       | 14.5             | 9.00         | TL        | 156/150    | M            | 1076                  | 312                | 850                      | 4000/3350                  |




Only fit for Prime tractor & Semi trailer

### PERFORMANCE DESCRIPTION:

- Suitable for short/middle distance,running on mixed pavements and secondary road.
- Large-scale and longitudinal groove mixed pattern,excellent driving force and braking force.
- Wide driving surface design,longer wear life.

## MX921



| SIZE        | PLY RATING | TREAD DEPTH (MM) | STANDARD RIM | TUBE TYPE | LOAD INDEX | SPEED SYMBOL | OVERALL DIAMETER (MM) | SECTION WIDTH (MM) | INFLATION PRESSURE (KPA) | MAX LOAD(KG) (SINGLE/DUAL) |
|-------------|------------|------------------|--------------|-----------|------------|--------------|-----------------------|--------------------|--------------------------|----------------------------|
| 11R24.5     | 18PR       | 14.0             | 8.25         | TL        | 152/149    | M            | 1104                  | 279                | 830                      | 3250/3000                  |
| 11R22.5     | 18PR       | 14.5             | 8.25         | TL        | 149/146    | M            | 1054                  | 279                | 830                      | 3000/2725                  |
| 295/75R22.5 | 16PR       | 14.0             | 9.00         | TL        | 146/143    | L            | 1014                  | 298                | 830                      | 3000/2725                  |
| 295/80R22.5 | 18PR       | 14.5             | 9.00         | TL        | 152/149    | M            | 1044                  | 298                | 900                      | 3550/3250                  |
| 315/80R22.5 | 20PR       | 14.5             | 9.00         | TL        | 156/150    | M            | 1076                  | 312                | 850                      | 4000/3350                  |




Only fit for Prime tractor & Semi trailer

### PERFORMANCE DESCRIPTION:

- All positions,fit for medium,long distance and high speed driving on well paved road.
- High speed performance and good driveability.
- Low-heat generation,low noise emission,good grip performance.

## MX906



| SIZE        | PLY RATING | TREAD DEPTH (MM) | STANDARD RIM | TUBE TYPE | LOAD INDEX | SPEED SYMBOL | OVERALL DIAMETER (MM) | SECTION WIDTH (MM) | INFLATION PRESSURE (KPA) | MAX LOAD(KG) (SINGLE/DUAL) |
|-------------|------------|------------------|--------------|-----------|------------|--------------|-----------------------|--------------------|--------------------------|----------------------------|
| 385/65R22.5 | 20PR       | 14.5             | 11.75        | TL        | 160        | K            | 1072                  | 288                | 900                      | 4500/--                    |



# MARVEMAX<sup>®</sup> HIGH COST-EFFECTIVE TIRES

TRAILER / DRIVE




Only fit for Prime tractor & Semi trailer

## PERFORMANCE DESCRIPTION:

- Suitable for short/middle distance, running on mixed pavements and secondary road.
- Large-scale and longitudinal groove mixed pattern, excellent driving force and braking force.
- Wide driving surface design, longer wear life.

TRAILER

## MX922



| SIZE        | PLY RATING | TREAD DEPTH (MM) | STANDARD RIM | TUBE TYPE | LOAD INDEX | SPEED SYMBOL | OVERALL DIAMETER (MM) | SECTION WIDTH (MM) | INFLATION PRESSURE (KPA) | MAX LOAD (KG) [SINGLE/DUAL] |
|-------------|------------|------------------|--------------|-----------|------------|--------------|-----------------------|--------------------|--------------------------|-----------------------------|
| 385/65R22.5 | 20PR       | 14.5             | 11.75        | TL        | 160        | K            | 1072                  | 288                | 900                      | 4500/--                     |



Only fit for Prime tractor & Semi trailer

## PERFORMANCE DESCRIPTION:

- Applied for low speed, mining, gravel etc, bad road conditions.
- Deepened pattern and simple big block design, special tread compound providing outstanding anti pricking and anti chunking ability.
- Excellent driving force and braking force. Good grip performance on all kinds of complex roads.

DRIVE

## MX910



| SIZE    | PLY RATING | TREAD DEPTH (MM) | STANDARD RIM | TUBE TYPE | LOAD INDEX | SPEED SYMBOL | OVERALL DIAMETER (MM) | SECTION WIDTH (MM) | INFLATION PRESSURE (KPA) | MAX LOAD (KG) [SINGLE/DUAL] |
|---------|------------|------------------|--------------|-----------|------------|--------------|-----------------------|--------------------|--------------------------|-----------------------------|
| 12R22.5 | 18PR       | 23.0             | 9.00         | TL        | 152/149    | L            | 1096                  | 300                | 930                      | 3550/3250                   |



Only fit for Prime tractor & Semi trailer

## PERFORMANCE DESCRIPTION:

- Applied for low speed, mining, gravel etc, bad road conditions.
- Deepened pattern and simple big block design, special tread compound providing outstanding anti pricking and anti chunking ability.
- Excellent driving force and braking force. Good grip performance on all kinds of complex roads.

DRIVE

## MX908



| SIZE     | PLY RATING | TREAD DEPTH (MM) | STANDARD RIM | TUBE TYPE | LOAD INDEX | SPEED SYMBOL | OVERALL DIAMETER (MM) | SECTION WIDTH (MM) | INFLATION PRESSURE (KPA) | MAX LOAD (KG) [SINGLE/DUAL] |
|----------|------------|------------------|--------------|-----------|------------|--------------|-----------------------|--------------------|--------------------------|-----------------------------|
| 11.00R20 | 18PR       | 23.0             | 8.00         | TT        | 152/149    | F            | 1085                  | 293                | 930                      | 3550/3250                   |
| 12.00R20 | 20PR       | 23.5             | 8.50         | TT        | 156/153    | F            | 1135                  | 315                | 900                      | 4000/3650                   |




Only fit for Prime tractor & Semi trailer

## PERFORMANCE DESCRIPTION:

- Suitable for short/middle distance, running on mixed pavements and secondary road.
- Large-scale and longitudinal groove mixed pattern, excellent driving force and braking force.
- Wide driving surface design, longer wear life.

DRIVE

## MX911



| SIZE     | PLY RATING | TREAD DEPTH (MM) | STANDARD RIM | TUBE TYPE | LOAD INDEX | SPEED SYMBOL | OVERALL DIAMETER (MM) | SECTION WIDTH (MM) | INFLATION PRESSURE (KPA) | MAX LOAD (KG) [SINGLE/DUAL] |
|----------|------------|------------------|--------------|-----------|------------|--------------|-----------------------|--------------------|--------------------------|-----------------------------|
| 12.00R20 | 20PR       | 18.5             | 8.50         | TT        | 156/153    | L            | 1125                  | 315                | 900                      | 4000/3650                   |
| 13R22.5  | 20PR       | 21.0             | 9.75         | TL        | 154/151    | L            | 1124                  | 320                | 875                      | 4000/3350                   |



# MARVEMAX<sup>®</sup> HIGH COST-EFFECTIVE TIRES




Only fit for Prime tractor & Semi trailer

PERFORMANCE DESCRIPTION:

- For driving on mixed road ,low speed ,short distance.
- Large pattern with stiffener and staggered pattern design provides good driving and braking performance.
- Deep pattern design for longer lifetime.

DRIVE

MX925



| SIZE     | PLY RATING | TREAD DEPTH (MM) | STANDARD RIM | TUBE TYPE | LOAD INDEX | SPEED SYMBOL | OVERALL DIAMETER (MM) | SECTION WIDTH (MM) | INFLATION PRESSURE (KPA) | MAX LOAD(KG) [SINGLE/DUAL] |
|----------|------------|------------------|--------------|-----------|------------|--------------|-----------------------|--------------------|--------------------------|----------------------------|
| 11.00R20 | 18PR       | 17.5             | 8.00         | TT        | 152/149    | L            | 1085                  | 293                | 930                      | 3550/3250                  |
| 12.00R20 | 20PR       | 18.5             | 8.50         | TT        | 156/153    | L            | 1125                  | 315                | 900                      | 4000/3650                  |




Only fit for Prime tractor & Semi trailer

PERFORMANCE DESCRIPTION:

- Suitable for short/middle distance,running on mixed pavements and secondary road.
- Large-scale and longitudinal groove mixed pattern,excellent driving force and braking force.
- Wide driving surface design,longer wear life.

DRIVE

MX959



| SIZE    | PLY RATING | TREAD DEPTH (MM) | STANDARD RIM | TUBE TYPE | LOAD INDEX | SPEED SYMBOL | OVERALL DIAMETER (MM) | SECTION WIDTH (MM) | INFLATION PRESSURE (KPA) | MAX LOAD(KG) [SINGLE/DUAL] |
|---------|------------|------------------|--------------|-----------|------------|--------------|-----------------------|--------------------|--------------------------|----------------------------|
| 11R22.5 | 18PR       | 18.5             | 8.25         | TL        | 149/146    | L            | 1065                  | 279                | 830                      | 3250/3000                  |
| 13R22.5 | 20PR       | 18.5             | 9.75         | TL        | 154/151    | L            | 1124                  | 235                | 830                      | 3750/3450                  |



Only fit for Prime tractor & Semi trailer

PERFORMANCE DESCRIPTION:

- Suitable for short/middle distance,running on mixed pavements and secondary road.
- Large-scale and longititudianl groove mixed pattern,excellent driving force and braking force.
- Strong durability and overload performance.

DRIVE

MX952



| SIZE     | PLY RATING | TREAD DEPTH (MM) | STANDARD RIM | TUBE TYPE | LOAD INDEX | SPEED SYMBOL | OVERALL DIAMETER (MM) | SECTION WIDTH (MM) | INFLATION PRESSURE (KPA) | MAX LOAD(KG) [SINGLE/DUAL] |
|----------|------------|------------------|--------------|-----------|------------|--------------|-----------------------|--------------------|--------------------------|----------------------------|
| 11.00R20 | 18PR       | 17.5             | 8.00         | TT        | 152/149    | L            | 1085                  | 293                | 930                      | 3550/3250                  |
| 12.00R20 | 20PR       | 18.5             | 8.50         | TT        | 156/153    | L            | 1125                  | 315                | 900                      | 4000/3650                  |



Only fit for Prime tractor & Semi trailer

PERFORMANCE DESCRIPTION:

- Suitable for short/middle distance,running on mixed pavements and secondary road.
- Large-scale and longitudinal groove mixed pattern,excellent driving force and braking force.
- Wide driving surface design,longer wear life.

DRIVE

MX968



| SIZE        | PLY RATING | TREAD DEPTH (MM) | STANDARD RIM | TUBE TYPE | LOAD INDEX | SPEED SYMBOL | OVERALL DIAMETER (MM) | SECTION WIDTH (MM) | INFLATION PRESSURE (KPA) | MAX LOAD(KG) [SINGLE/DUAL] |
|-------------|------------|------------------|--------------|-----------|------------|--------------|-----------------------|--------------------|--------------------------|----------------------------|
| 12R22.5     | 18PR       | 19.0             | 9.00         | TL        | 152/149    | L            | 1094                  | 300                | 930                      | 3550/3250                  |
| 295/80R22.5 | 18PR       | 19.5             | 9.00         | TL        | 152/149    | L            | 1044                  | 298                | 900                      | 3550/3250                  |
| 315/80R22.5 | 20PR       | 19.0             | 9.00         | TL        | 156/150    | L            | 1076                  | 312                | 850                      | 4000/3350                  |



# MARVEMAX<sup>®</sup> HIGH COST-EFFECTIVE TIRES

DRIVE / ALL POSITION




Only fit for Prime tractor & Semi trailer

## PERFORMANCE DESCRIPTION:

- Medium and long distance ,high speed on well paved road.
- The middle block design and the shoulder closed design ensure the grip of the tire and reduce the rolling resistance of the tire.
- Special block pattern design ,with higher driving force,excellent ground rolling resistance performance.

DRIVE



## MX969

| SIZE        | PLY RATING | TREAD DEPTH (MM) | STANDARD RIM | TUBE TYPE | LOAD INDEX | SPEED SYMBOL | OVERALL DIAMETER (MM) | SECTION WIDTH (MM) | INFLATION PRESSURE (KPA) | MAX LOAD(KG) [SINGLE/DUAL] |
|-------------|------------|------------------|--------------|-----------|------------|--------------|-----------------------|--------------------|--------------------------|----------------------------|
| 11R22.5     | 18PR       | 19.5             | 8.25         | TL        | 149/146    | L            | 1065                  | 279                | 930                      | 3250/3000                  |
| 11R24.5     | 18PR       | 19.5             | 8.25         | TL        | 152/149    | L            | 1116                  | 279                | 830                      | 3250/3000                  |
| 295/75R22.5 | 16PR       | 19.5             | 9.00         | TL        | 146/143    | L            | 1014                  | 298                | 830                      | 3000/2725                  |



Only fit for Prime tractor & Semi trailer

## PERFORMANCE DESCRIPTION:

- Applied for low speed,mining,gravel etc,bad road conditions.
- Optimize the layout design of pattern block and groove angle provides excellent traction performance.
- The design of tear resistant tread formula makes,its tread lift more tear resistant.

DRIVE



## MX993

| SIZE     | PLY RATING | TREAD DEPTH (MM) | STANDARD RIM | TUBE TYPE | LOAD INDEX | SPEED SYMBOL | OVERALL DIAMETER (MM) | SECTION WIDTH (MM) | INFLATION PRESSURE (KPA) | MAX LOAD(KG) [SINGLE/DUAL] |
|----------|------------|------------------|--------------|-----------|------------|--------------|-----------------------|--------------------|--------------------------|----------------------------|
| 11.00R20 | 18PR       | 23.0             | 8.00         | TT        | 152/149    | F            | 1095                  | 293                | 930                      | 3550/3250                  |
| 12.00R20 | 20PR       | 23.5             | 8.50         | TT        | 156/153    | F            | 1135                  | 315                | 900                      | 4000/3650                  |




Only fit for Prime tractor & Semi trailer

## PERFORMANCE DESCRIPTION:

- Mainly applicable to the drive shaft of vehicles with fixed load,long distance and high speed driving on good pavement.
- Deep groove and wide driving surface design,with superior high wear life.
- Special block pattern design,with higher braking and driving.

DRIVE



## MX970

| SIZE        | PLY RATING | TREAD DEPTH (MM) | STANDARD RIM | TUBE TYPE | LOAD INDEX | SPEED SYMBOL | OVERALL DIAMETER (MM) | SECTION WIDTH (MM) | INFLATION PRESSURE (KPA) | MAX LOAD(KG) [SINGLE/DUAL] |
|-------------|------------|------------------|--------------|-----------|------------|--------------|-----------------------|--------------------|--------------------------|----------------------------|
| 12R22.5     | 18PR       | 19.0             | 9.00         | TL        | 152/149    | L            | 1085                  | 300                | 900                      | 3550/3250                  |
| 295/80R22.5 | 18PR       | 19.5             | 9.00         | TL        | 152/149    | L            | 1044                  | 298                | 900                      | 3550/3250                  |
| 315/80R22.5 | 20PR       | 19.0             | 9.00         | TL        | 156/150    | L            | 1082                  | 312                | 850                      | 4000/3350                  |




Only fit for Prime tractor & Semi trailer

## PERFORMANCE DESCRIPTION:

- All positions,fit for medium and long distance,high speed on well paved road.
- Zigzag groove and shoulder groove design,excellent drive performance handling performance.
- Widened running surface and optimized grounding pressure,outstanding wear resistance.

ALL POSITION



## MX096

| SIZE     | PLY RATING | TREAD DEPTH (MM) | STANDARD RIM | TUBE TYPE | LOAD INDEX | SPEED SYMBOL | OVERALL DIAMETER (MM) | SECTION WIDTH (MM) | INFLATION PRESSURE (KPA) | MAX LOAD(KG) [SINGLE/DUAL] |
|----------|------------|------------------|--------------|-----------|------------|--------------|-----------------------|--------------------|--------------------------|----------------------------|
| 12.00R24 | 20PR       | 14.5             | 8.50         | TT        | 160/157    | K            | 1226                  | 315                | 900                      | 4500/4125                  |



# MARVEMAX<sup>®</sup> HIGH COST-EFFECTIVE TIRES




Only fit for Prime tractor & Semi trailer

PERFORMANCE DESCRIPTION:

- All positions, fit for medium and long distance, high speed on well paved road.
- Excellent drive performance and handling performance.
- Widened running surface and optimized grounding pressure, outstanding wear resistance.

ALL POSITION



MX098

| SIZE     | PLY RATING | TREAD DEPTH (MM) | STANDARD RIM | TUBE TYPE | LOAD INDEX | SPEED SYMBOL | OVERALL DIAMETER (MM) | SECTION WIDTH (MM) | INFLATION PRESSURE (KPA) | MAX LOAD (KG) [SINGLE/DUAL] |
|----------|------------|------------------|--------------|-----------|------------|--------------|-----------------------|--------------------|--------------------------|-----------------------------|
| 12.00R24 | 20PR       | 14.5             | 8.50         | TT        | 160/157    | K            | 1226                  | 315                | 900                      | 4500/4125                   |




Only fit for Prime tractor & Semi trailer

PERFORMANCE DESCRIPTION:

- All position, applied for highway, urban and country road.
- Three rib pattern, extra sideslip resistance, delivers superior stability and drainage of driving.

ALL POSITION



MX901

| SIZE     | PLY RATING | TREAD DEPTH (MM) | STANDARD RIM | TUBE TYPE | LOAD INDEX | SPEED SYMBOL | OVERALL DIAMETER (MM) | SECTION WIDTH (MM) | INFLATION PRESSURE (KPA) | MAX LOAD (KG) [SINGLE/DUAL] |
|----------|------------|------------------|--------------|-----------|------------|--------------|-----------------------|--------------------|--------------------------|-----------------------------|
| 11.00R20 | 18PR       | 17.0             | 8.00         | TT        | 152/149    | L            | 1085                  | 293                | 930                      | 3550/3250                   |
| 12.00R20 | 20PR       | 16.0             | 8.50         | TT        | 156/153    | L            | 1125                  | 315                | 900                      | 4000/3650                   |
| 12R22.5  | 18PR       | 15.0             | 9.00         | TL        | 152/149    | M            | 1085                  | 300                | 930                      | 3550/3250                   |




Only fit for Prime tractor & Semi trailer

PERFORMANCE DESCRIPTION:

- All positions, fit for driving on various roads.
- Mature pattern design, superior traction performance, braking performance and wet sliding resistance.
- High efficiency of heat dissipation and strong driving force due to large tread groove on shoulder.

ALL POSITION



MX902 /MX902+

| SIZE          | PLY RATING | TREAD DEPTH (MM) | STANDARD RIM | TUBE TYPE | LOAD INDEX | SPEED SYMBOL | OVERALL DIAMETER (MM) | SECTION WIDTH (MM) | INFLATION PRESSURE (KPA) | MAX LOAD (KG) [SINGLE/DUAL] |
|---------------|------------|------------------|--------------|-----------|------------|--------------|-----------------------|--------------------|--------------------------|-----------------------------|
| 11.00R20      | 18PR       | 17.0             | 8.00         | TT        | 152/149    | L            | 1085                  | 293                | 930                      | 3550/3250                   |
| 12.00R20      | 20PR       | 16.0             | 8.50         | TT        | 156/153    | L            | 1125                  | 315                | 900                      | 4000/3650                   |
| 12.00R24      | 20PR       | 14.5             | 8.50         | TT        | 160/157    | K            | 1226                  | 315                | 900                      | 4500/4125                   |
| 11R22.5       | 18PR       | 14.5             | 8.25         | TL        | 149/146    | M            | 1054                  | 279                | 830                      | 3000/2725                   |
| 12R22.5       | 18PR       | 15.0             | 9.00         | TL        | 152/149    | M            | 1085                  | 300                | 930                      | 3550/3250                   |
| 13R22.5       | 20PR       | 16.0             | 9.75         | TL        | 154/151    | M            | 1124                  | 320                | 830                      | 3750/3450                   |
| 295/80R22.5   | 18PR       | 14.0             | 9.00         | TL        | 152/149    | M            | 1044                  | 298                | 900                      | 3550/3250                   |
| ☆ 315/80R22.5 | 20PR       | 14.5             | 9.00         | TL        | 156/150    | M            | 1076                  | 312                | 850                      | 4000/3350                   |




Only fit for Prime tractor & Semi trailer

PERFORMANCE DESCRIPTION:

- All positions, fit for medium and long distance, high speed on well paved road.
- Excellent drive performance and handling performance.
- Widened running surface and optimized grounding pressure, outstanding wear resistance.

ALL POSITION



MX986

| SIZE    | PLY RATING | TREAD DEPTH (MM) | STANDARD RIM | TUBE TYPE | LOAD INDEX | SPEED SYMBOL | OVERALL DIAMETER (MM) | SECTION WIDTH (MM) | INFLATION PRESSURE (KPA) | MAX LOAD (KG) [SINGLE/DUAL] |
|---------|------------|------------------|--------------|-----------|------------|--------------|-----------------------|--------------------|--------------------------|-----------------------------|
| 12R22.5 | 18PR       | 15.0             | 9.00         | TL        | 152/149    | M            | 1085                  | 300                | 930                      | 3550/3250                   |

# SPEED SYMBOL

# LOAD CAPACITY INDEX

| Speed Symbol | Speed(km/h) | Speed Symbol | Speed(km/h) |
|--------------|-------------|--------------|-------------|
| B            | 50          | M            | 130         |
| C            | 60          | N            | 140         |
| D            | 65          | P            | 150         |
| E            | 70          | Q            | 160         |
| F            | 80          | R            | 170         |
| G            | 90          | S            | 180         |
| J            | 100         | T            | 190         |
| K            | 110         | U            | 200         |
| L            | 120         | H            | 210         |

| LI  | KG   | LI  | KG   | LI  | KG   |
|-----|------|-----|------|-----|------|
| 115 | 1215 | 136 | 2240 | 157 | 4125 |
| 116 | 1250 | 137 | 2300 | 158 | 4250 |
| 117 | 1285 | 138 | 2360 | 159 | 4375 |
| 118 | 1320 | 139 | 2430 | 160 | 4500 |
| 119 | 1360 | 140 | 2500 | 161 | 4625 |
| 120 | 1400 | 141 | 2575 | 162 | 4750 |
| 121 | 1450 | 142 | 2650 | 163 | 4875 |
| 122 | 1500 | 143 | 2725 | 164 | 5000 |
| 123 | 1550 | 144 | 2800 | 165 | 5150 |
| 124 | 1600 | 145 | 2900 | 166 | 5300 |
| 125 | 1650 | 146 | 3000 | 167 | 5450 |
| 126 | 1700 | 147 | 3075 | 168 | 5600 |
| 127 | 1750 | 148 | 3150 | 169 | 5800 |
| 128 | 1800 | 149 | 3250 | 170 | 6000 |
| 129 | 1850 | 150 | 3350 | 171 | 6150 |
| 130 | 1900 | 151 | 3450 | 172 | 6300 |
| 131 | 1950 | 152 | 3550 | 173 | 6500 |
| 132 | 2000 | 153 | 3650 | 174 | 6700 |
| 133 | 2060 | 154 | 3750 | 175 | 6900 |
| 134 | 2120 | 155 | 3875 | 176 | 7100 |
| 135 | 2180 | 156 | 4000 | 177 | 7300 |



 Off the road/Only fit for Mine truck

### PERFORMANCE DESCRIPTION:

- Applied for low speed,mining,gravel etc,bad road conditions.
- Deepened pattern and simple big block design,special tread compound providing outstanding anti pricking and anti chunking ability.
- Excellent driving force and braking force.Good grip performance on all kinds of complex roads.

**MX992**



| SIZE    | PLY RATING | TREAD DEPTH (MM) | STANDARD RIM | TUBE TYPE | LOAD INDEX | SPEED SYMBOL | OVERALL DIAMETER (MM) | SECTION WIDTH (MM) | INFLATION PRESSURE (KPA) | MAX LOAD(KG) [SINGLE/DUAL] |
|---------|------------|------------------|--------------|-----------|------------|--------------|-----------------------|--------------------|--------------------------|----------------------------|
| 12R22.5 | 18PR       | 24.0             | 9.00         | TL        | 152/149    | A8           | 1096                  | 300                | 930                      | 3550/3250                  |